

20" Throat
with 16" or 24"
Under the Guide

MODEL V20 & V20-24

Vertical Bandsaw



Manufactured in the United States of America

Wellsaw®
Built better to work stronger and last longer

V20 & V20-24

Models V20 & V20-24 Vertical Bandsaws



Standard Features

Heavy Tube Steel Frame

Precision Ground Cast Iron Table with Replaceable Throat Plate

Unique Heavy Duty Roller Guides

Rotate 90° to Accommodate Long Materials

Baldor® Motor

Magnetic Starter with Undervoltage and Overload Protection

115 Volts at Controls

Two Speed Cast Iron Gearbox with Helical Gears and Oil Bath Lubrication for Quiet Operation

Blade Speed Indicator

Blade Tension Indicator

Flexible Arm Worklight

Chip Blower (Shop Air)

Removable Chip Tray

Tiger-Tooth® Bi-Metal Blade

OSHA Blade Guarding

Rotary Blade Brush

Available Factory Installed Options

Ideal® Blade Welder, Grinder and Shear

24" Extended Height (Model V20-24)

Miter Gauge

Rip Fence, 26"

1" Blade (Not Available on V-20-24)

Vector AC Drive Variable Bandspeed

Spray Mist Coolant System

Vacuum Nozzle

Extension Table

Stock Stand

5' and 10' Non-Powered Roller Conveyor

J.I.C. or NFPA Electrics (with Fused Disconnect)

Consult Factory for Additional Options

Specifications

Capacity

Throat 20" Deep

Table to Guide 16" High

V-20-24 24" High

Blade Size

Standard 3/16" through 3/4"

Optional 1/2" through 1"

(This Option Not Available on V-20-24)

Blade Length

14'9" (177")

V-20-24 16'1" (193")

Band Wheels

21" Cast Aluminum with Replacable Rubber Tires

Blade Speeds

Low Range 45-400 SFPM

High Range 325-3000 SFPM

Blade Guides

Sealed Ball Bearings with 90° Rotation Feature

Table Size

26" x 26" Cast Iron

Tilt

5° Inside and 45° Outside

Height

37-1/2"

Drive Motor

Three Phase 3hp 208/230/460 Volt

Single Phase 2hp 115/208/230 Volt

Floor Area

32" Wide x 48" Deep

Height Standard

83-1/2"

V-20-24 91-1/2"

Shipping Weight

Standard 950 Lbs.

V-20-24 1050 Lbs.

Wellsaw®