



16645 Heimbach Road
Three Rivers, MI 49093
Phone: (269) 279-5123
Fax: (269) 279-6337
www.wfwells.com

J2008

W.F. WELLS MODEL H-2024-1

EFFECTIVE June 1, 2008*

Specifications

Capacity	Rectangular at 90° 20" High x 24" Wide, Round at 90° 20" Diameter		
Weight Capacity	5,000 lbs		
Blade Speed	60-500 SFPM		
Blade Size	1¼" X .042" X 17' -8"		
Blade Guide	Rollers and Carbide Side Blocks		
Blade Tension	Manual with Indicator		
Bandwheel Size	20"	<u>Voltage</u>	<u>Order Number</u>
Vise	Manual, 15"	208-60-3	0010815
Blade Drive	7½ HP, AC Vector Drive	230-60-3	0010816
Sawing Force	30-120 lbs	460-60-3	0010817
Coolant Capacity	15 Gallons	575-60-3	0010818
Hydraulic Capacity	¾ Gallon		
Hydraulic Drive	½ HP Motor		
Work Height	26"		
Shipping Weight	2,800 lbs		
Electrics	Wired to NFPA 79 Machine Tool Standards		

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

Order Number

Air Vise, Manual	0056026
Air Holddown, Manual	0056037
Automatic Length Stop Assembly	0056707
Discharge Worktable, 24" W x 48" L with Stock Stop	0056041
Work Light, Wired In	0052021
Blade Break/Stall Switch	0056040
Electronic Chip Conveyor, Auger Style	0056036
Electronic Powered Conveyor 21" X 10'	0056202
High Speed Drive & Guides (1" Blade) 400-3000 SFPM	0051045
Free Standing Roller Stock Conveyors, 6" Centers	
21" X 5' X 5,000 lbs Cap. Distributed Weight	0050247
21" X 10' X 10,000 lbs Cap. Distributed Weight	0050250
24" X 5' X 5,000 lbs Cap. Distributed Weight	0056262
24" X 10' X 10,000 lbs Cap. Distributed Weight	0056263
24" Powered Conveyor	Consult Factory for Pricing

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

MADE IN USA