



16645 Heimbach Road
Three Rivers, MI 49093
Phone: 269-279-5123
Fax: 269-279-6337
www.wfwells.com

J2008

W.F. WELLS MODEL H-2024-3C (3° Cant)

Specifications

Capacity	Rectangular @ 90° 19½" H x 24" W, Round at 90° 20" Diameter		
Weight Capacity.....	5,000 lbs		
Blade Speed	60-500 SFPM		
Blade Size	1½" X .050" X 20'-0"		
Blade Guide	Roller Guides with Carbide Inserts		
Blade Tension	Hydraulic		
Bandwheel Size	20"	<u>Voltage</u>	<u>Order Number</u>
Vise	Manual or Full Stroke Hydraulic, 15"	208-60-3	0010835
Blade Drive	10 HP, AC Vector Drive	230-60-3	0010836
Sawing Force	0-750 lbs	460-60-3	0010837
Coolant Capacity	15 Gallons	575-60-3	0010838
Hydraulic Capacity	20 Gallons		
Hydraulic Drive.....	2 HP Motor		
Work Height	35"		
Shipping Weight.....	3,900 lbs		
Electrics	Wired to NFPA 79 Machine Tool Standards		

OPTIONAL FACTORY INSTALLED ACCESSORIES

<u>Description</u>	<u>Order Number</u>
Hydraulic Holddown, Manual	0056038
Automatic Length Stop Assembly	0056707
Discharge Worktable, 20" X 48" L with Stock Stop	0056041
Extra Coolant Nozzle (Mag Base)	0011681
Work Light, Wired In	0052021
Blade Break/Stall Switch	0056040
Hydraulic Chip Conveyor, Auger Style	0056036
High Speed Drive & Guides (1" Blade) 400-3000 SFPM	0051045
21" X 10' Powered Conveyor, Hydraulic	0056202
Free Standing Roller Stock Conveyors, 6" Centers	
21" X 5' X 5,000 lbs Cap. Distributed Weight	0050247
21" X 10' X 10,000 lbs Cap. Distributed Weight	0050250
24" X 5' X 5,000 lbs Cap. Distributed Weight	0056262
24" X 10' X 10,000 lbs Cap. Distributed Weight	0056263
24" Powered Conveyor	Consult Factory for Pricing

Consult Factory for Additional Accessories

MADE IN USA