



16645 Heimbach Road
Three Rivers, MI 49093
Phone 269-279-5123
Fax 269-279-6337
www.wfwells.com

J2008

W. F. WELLS MODEL S-40-4
EFFECTIVE June 1, 2008*

Specifications

Capacity	Rectangular at 90° 40" H x 40" W @ 45° 40" H x 24" W
Weight Capacity	15,000 lbs
Blade Speed	60-500 SFPM
Blade Size	2 ⁵ / ₈ " X .063" X 29'
Blade Guide	Carbide Blocks, Spring Tensioned
Blade Tension	Hydraulic
Bandwheel Size	42"
Vise	Hydraulic Full Stroke
Blade Drive	15 HP, AC Vector Drive
Positive Sawing Force	0-1000 lbs
Coolant Capacity	20 Gallons
Hydraulic Capacity	20 Gallons
Hydraulic Drive	5 HP Motor
Work Height	28"
Vise Jaw Height	24"
Hydraulic Chip Conveyor	
Hydraulic Powered Blade Brush	
Hydraulic Guide Arm Positioning	
Blade Tension Indicator	
Blade Break/Stall Switch	
Shipping Weight	10,500 lbs
Electrics	LED Blade Speed Indicator, LED Positive Feed Readout Wired to NFPA 79 Machine Tool Standards

Order

Number

Voltage

208-60-3

0011120

230-60-3

0011121

460-60-3

0011122

575-60-3

0011123

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

Order Number

Discharge Worktable 40" W X 56" L

0056241

Hydraulic Holddown, Saw Vise

0056243

Outboard Vise with Hydraulic Holddown

0056245

Outboard Vise

0056244

Hydraulic Powered Conveyor 36" X 10'

0056200

Non-Powered Conveyor 36" X 5'

0056198

Non-Powered Conveyor 36" X 10'

0056199

40" Conveyor

Consult Factory for Pricing

Roller Bed Inserts (3¹/₂" X .300" Rollers)

0056252

High Speed Drive & Guides (1¹/₂" Blade) 400-3000 SFPM

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

MADE IN USA