



16645 Heimbach Road
Three Rivers, MI 49093
Phone 269-279-5123
Fax 269-279-6337
www.wfwells.com

J2008

W. F. WELLS MODEL S-40-3C (6° Cant)

Specifications

Capacity	Rectangular at 90° 37" H X 40" W		
	Rectangular at 45° 37" H X 24" W		
Weight Capacity	15,000 lbs		
Blade Speed	60-500 SFPM		
Blade Size	2" X .063" X 29'		
Blade Guide	Carbide Blocks, Spring Tensioned with Idle Roller Back-up		
Blade Tension	Hydraulic		
Bandwheel Size	42"	<u>Voltage</u>	<u>Order Number</u>
Vise	Hydraulic	208-60-3	0011102
Blade Drive	15 HP, AC Vector Drive	230-60-3	0011103
Hydraulic Drive.....	5 HP	460-60-3	0011104
Sawing Force	0-1,000 lbs	575-60-3	0011105
Coolant Capacity.....	15 Gallons		
Hydraulic Capacity	20 Gallons		
Work Height	34"		
Outfeed Table	24" X 40"		
Vise Jaw Height	24"		
Hydraulic Powered Blade Brush			
Hydraulic Positioned Guide Arm			
Blade Tension Indicator			
Blade Break/Stall Switch			
Shipping Weight.....	9,200 lbs		
Electrics	Wired to NFPA 79 Machine Tool Standards		

OPTIONAL FACTORY INSTALLED ACCESSORIES

<u>Description</u>	<u>Order Number</u>
Discharge Worktable 40" Wide X 56" Long	0056225
Hydraulic Chip Conveyor	0056230
Hydraulic Holddown, Saw Vise	0056224
Outboard Vise with Hydraulic Holddown	0056231
Outboard Vise	0056232
High Speed Drive & Guides (1½" Blade) 400-3000 SFPM	
Hydraulic Powered Conveyor 36" X 10'	0056513
Non-Powered Conveyor 36" X 5'	0056512
Non-Powered Conveyor 36" X 10'	0056511
40" Conveyor	Consult Factory for Pricing

Consult Factory for Additional Accessories

MADE IN USA