



Model B-2575-3

Semi-Automatic
Twin Post Bandsaw



MADE IN THE USA

MACHINE SPECIFICATIONS

Capacity	25" High x 80" Wide
Weight Capacity	15,000 lbs
Blade Speed	60-500 SFPM
Blade Size	2" X .063" X 33'-6" (2-5/8" optional)
Blade Guide	Spring Tensioned Carbide Blocks w/ Idle Roller Backup
Blade Tension	Hydraulic
Bandwheel Size	26"
Vise	Hyd - 50" Stroke (full stroke optional)
Blade Drive	15 HP, AC Vector Drive
Sawing Force	0-1000 lbs
Coolant Delivery	Mist
Hydraulic Capacity	20 Gallons
Hydraulic Drive	5 HP Motor
Work Height	28"
Outfeed Table	Optional
Horizontal Vise Jaw	Optional Heights Available
Shipping Weight	10,000 lbs
Electrics	Wired to NFPA 79 Machine Tool Standards
Shipping Dimensions	48" L x 201" W x 105" H

STANDARD EQUIPMENT

2" Bi-Metal Blade
AC Vector Drive
Spring Loaded Carbide Guides
Hydraulic Vise Operation
Hydraulic Blade Tension
Semi-Automatic Operation
Mist Coolant System
Blade Tension Indicator
Hyd - Powered Blade Brush
TEFC Motors
Fused Disconnect with Lock-Out
Blade Break/Stall Switch
Console Controlled Blade Speed
Feed Pressure Monitor/Regulator
Low Voltage/Overload Protection
Electronic Door Safety Interlocks
Work Lights
Hydraulic Positioned Guide Arm
All Safety Guards
Operator Manual and Parts List
Remote Operators Console

Saw Shown with Optional Vertical "Grating" Holddown – Both Sides of Blade – Capacity 6" x 80"

*Specifications subject to change without notice

W.F. Wells, Inc.

16645 Heimbach Road • Three Rivers, MI 49093

Phone: (269) 279-5123 • Fax: (269) 279-6337

www.wfwells.com • E-mail: info@wfwells.com