



16645 Heimbach Road
Three Rivers, MI 49093
Phone 269-279-5123
Fax 269-279-6337
www.wfwells.com

J2008

W. F. WELLS MODEL B-25-3CA3 CNC (6° CANT)

Specifications

Capacity 22" High x 40" Wide (25" Round, 24" Square)
Weight Capacity 15,000 lbs
Blade Speed 60-500 SFPM
Blade Size 2" X .063" X 26'-6"
Blade Guide Spring Tensioned Carbide Blocks with Idle Roller Backup
Blade Tension Hydraulic
Bandwheel Size 26"
Vise Hydraulic
Blade Drive 15 HP, AC Vector Drive
Sawing Force 0-1,000 lbs
Coolant Capacity 15 Gallons
Hydraulic Capacity 20 Gallons
Hydraulic Drive 5 HP Motor
Work Height 34"
Outfeed Table 12" X 41"
Vise Jaw Height 17"
Barfeed Projection 0 - 36" CNC Controlled
Projection Accuracy +/- .002"
Shuttle Indexes Unlimited
Remnant End 14"
Shipping Weight 11,400 lbs
Electrics Wired to NFPA 79 Machine Tool Standards
Hydraulic Positioned Guide Arm, Powered Blade Brush, Blade Break/Stall Switch
CNC Programmable Controlled with Color Touch Screen
500+ Job Selection
Automatic Kerf Compensation

Voltage

208-60-3
230-60-3
460-60-3
575-60-3

Order Number

0010370
0010371
0010372
0010373

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

Discharge Worktable 40" Wide X 56" Long
Optional Barfeed AF-12 40" Wide X 144" Stroke
Hydraulic Chip Conveyor
Hydraulic Holddown, Saw Vise
Hydraulic Holddown, Barfeed Vise
Outboard Vise with Hydraulic Holddown
Outboard Vise
Non-Powered Conveyor 36" X 5'
Non-Powered Conveyor 36" X 10'
40" Conveyor
High Speed Drive & Guides (1½" Blade) 500-3000 SFPM

Order Number

0056061
0050089
0056069
0056064
0050107
0056063
0056062
0052512
0052511
Consult Factory for Pricing

Consult Factory for Additional Accessories

MADE IN USA