



every solution is **unique.**

R050 Platform

Refrigerated Water Recirculating Systems

R050 platform

	with air cooled condenser	with water cooled condenser
Cooling Capacity (at 65°F/18°C supply water temp.)	Watts 1,400 Btu/Hr 4,775	Watts 1,750 Btu/Hr 5,970
Compressor HP	1/2	1/2
Refrigerant alternatives available	R134a	R134a
Water Pump Capacity alternatives available	1 GPM (3.8 LPM)	1 GPM (3.8 LPM)
Pump Motor HP	1/3	1/3
Reservoir Volume	5 Gallons (19 Liters)	5 Gallons (19 Liters)
Power Requirements ¹ alternatives available	115V-1Ø-60Hz 208/230V-1Ø-60Hz	115V-1Ø-60Hz 208/230V-1Ø-60Hz
Dimensions (W x D x H)	46 x 69 x 74 cm 18 x 27 x 29 in.	46 x 69 x 74 cm 18 x 27 x 29 in.
Shipping Weight	250 Lbs. (113 Kg)	250 Lbs. (113 Kg)

- **Unit specifications will change by adding certain options.**
- Cooling capacity of air-cooled units is based on 80°F/27°C ambient air temperature. Allowable ambient temperature range is 55°F to 90°F (13°C to 32°C). Changes in air temperature will affect cooling capacity. See Haskris Options (I) and/or (J) to operate outside this range.

¹ Also available in 50Hz—contact Haskris



Haskris Company

100 Kelly Street
Elk Grove Village, Illinois
60007 USA

Phone: 001-847-956-6420

Fax: 001-847-956-6595

Email: sales@haskris.com