Hydraulic


Straight Folding Brakes Box and Pan Brakes


UNION FABRICATION



SIZE		410-6 / 412-6	612-6 / 616-6	810-6/812-6/816-6	1010-6/1014-6/1016-6	1216-6 / 1218-6	4018-6 / 4022-6	
76mm	3"	3	6	6	6	6	6	
101mm	4"	5	3	4	4	6	6	
127mm	5'	5	6	10	10	10	10	
152mm	6"	1	2	2	6	9	-11	
TOTAL		II	17	22	26	31	33	

MODEL	V-412 V-612 V-816	V-812 V-1014	V-1016	V-4022		V-816-6		V-1016-6 V-1218-6 V-1016-6	VH-412-6 VH-1014-6 VH-612-6 VH-1216-6 VH-812-6 VH-4016-6	
A	80	100	100	100						
В	16	25	SO	25						
c	50	50	50	50	50	50	50	50	50	
D	53	53	50	53	53	50	53	50	23	
€		0.00			150	150	150	150	150	
F					50	50	50	50	50	
G			-		30	50	30	25	30	
н					33	33	33	33	33	
1	40	53	53	53	40	40	53	53	100	





With:

NC angle control Hardened 2-piece fingers Hydraulic clamping Hydraulic bending Box depth to 6"

Optional:

NC backgauges 800mm or 1250mm Extra radius fingers Special custom fingers

MC	DDEL	VH-4I2-6	VH-4I0-6	VH-6I2-6	VH-610-6	VH-8I2-6	VH-810-6	VH-1014-6	VH-1010-6	VH-1216-6	VH-4018-6
BENDING CAPACITY	BENDING LENGTH	1220mm(48°)	1220mm(48°)	1830mm(72°)	1830mm(72°)	2440mm(96°)	2540mm(100°)	3048mm(I20°)	3048mm(I20°)	3700mm(145°)	4000mm(157°)
	MILD STEEL	2.5mm(I2GA)	3.5mm(IOGA)	2.5mm(12GA)	3.5mm(IOGA)	2.5mm(12GA)	3.5mm(IOGA)	2.0mm(14GA)	3.5mm(IOGA)	1.6mm(16GA)	1.2mm(18GA)
	STAINLESS STEEL	I.6mm(I6GA)	2.5mm(I2GA)	1.6mm(16GA)	2.5mm(I2GA)	1.6mm(16GA)	2.5mm(I2GA)	12mm(18GA)	2.5mm(I2GA)	(ADSS)mm8.0	0.6mm(24GA)
BENDING ANGLE		0435	0-135*	0-135*	0-135"	0-135	0-135	0-135	0-135	0-135	0-135
BEAM ADJUSTMENT		2Smm(i')	25mm(f*)	25mm(l*)	25mm(l*)	25mm(l')	25mm(l')	25mm(l*)	25mm(l*)	25mm(l*)	25mm(l*)
MIN REVERSE BEND		16mm(1/2")	25mm(13/16°)	16mm(1/2")	25mm(13/16°)	16mm(1/2")	25mm(13/16°)	16mm(1/2°)	25mm(13/16°)	16mm(1/2")	16mm(1/2*)
MOTOR (HP)		5	5	S	5	3	5	3	5	3	3
PACKING SIZE (mm)		2100 x 1150 x 1680	2100 x 1150 x 1750	2700 x II50 x I680	2800 x 1100 x 1750	3350 x 1150 x 1680	3350 x II50 x I800	3900 x II50 x I680	3900 x II50 x I800	4700 x 1200 x 1700	4850 x 1200 x 1700
PACKING WEIGHT		1000Kgs	1750Kgs	1900Kgs	2400Kgs	2360Kgs	2700Kgs	2650Kgs	3500Kgs	3200Kgs	3300Kgs



Standard Accessories for Euro-style NC-equipped folders:











- Standard segmented or straight upper blade
- ② ⑤ Gap clearance manual adjustor.
- 4 Hold-down pressure adjusted by hand-wheel.
- 6 Hydraulic pressure adjustable at front side.
- Three functions foot pedal.







- 1 2-Axes NC included as :
 - A. 7.4" Schneider TOUCH screen.
 - B. 20mm min. front distance.
 - C. 800mm back gauge range and sheet plate supporter.
- 2 Extended back gauge upto 1000/1250 mm.
- CE conformity machine.
- A Radius fingers or customized shape.