

HEM Horizontal Pivot: H130HA-C

Capacity: 20" W x 10" H, 16" W x 16" H (Square) • **Blade:** 1-1/2" x 17'0" x .050"

Motor: 10 HP • **Hydraulics:** 2 HP • **Bar-feed:** 0-24" (Multiple Index)



Standard Features

Swing-Away Console – All Function Control
Computer Controlled Feed System
24" Solid Discharge Table – Bolts to Saw
Full Stroking Vises
Adjustable Clamping Force
Push Button Blade Speed w/ LED Readout
Powered Guide Arm
Carbide Blade Guides
Roller Guides – Entry & Exit
Cut Watcher System
Adjustable Cutting Force & Feed Rate
Powered Blade Tension
Chip Auger System
Material Jogging
Vertical Alignment Roller on Feed
Flood Coolant System w/ Wash-Down Hose
Broken Blade & Out of Stock Indicators
Safety Guards
220V/440V/3PH Electrical Motor Requirement
– This is Not a Dual Voltage Machine

Proudly Made in the U.S.A.



Optional Features

0-48" Stroke Bar-Feed
Full Capacity Top Clamp – Main & Feed Vise
Reduced Capacity Top Clamp – Feed Vise
Reduced Capacity Top Clamp – Main Vise
Outboard Powered Vise on Discharge
3rd Holding Vise on Feed
Interlocking Vise Jaws
Laser Light System
Spray Mist Lubrication
Optional Control Consoles
5' or 10' Idle Roller Stock Table



www.hemsaw.com

Address: P.O. Box 1148 Pryor OK 74361 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HEM, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HEM, Inc. for a certified dimensional drawing of your specific model.
Copyright 112800 HEM, Inc. All rights reserved.