

HEM Horizontal Pivot: H90A-1

Capacity: 12.75" W x 12.75" H • **Blade:** 1" x 12'10" x .035"

Motor: 3 HP • **Bar-feed:** 0-24" (Single Index)



Standard Features

Console on Top of Saw - Bi-Function Control

18" Exit Support

Adjustable Main & Feed Vise

Adjustable Clamping Force

2 Hold Down Fixtures

Manual Guide Arm Adjustment

Push Button Blade Speed w/ LED Readout

Adjustable Cutting Force & Feed Rate

Carbide Blade Guides

Manual Blade Tension

Vertical Alignment Bar on Feed

Blade Brush

Flood Coolant System w/ Wash-Down Hose

Broken Blade & Out of Stock Indicators

Safety Guards

220V/440V/3PH Electrical Motor Requirement

– This is Not a Dual Voltage Machine

85 PSI, 4-6 CFM Minimum Air Requirement

(Equipped w/ Air Filter/Lubricator)

Proudly Made in the U.S.A.



Optional Features

Reduced Capacity Top Clamp – Feed Vise

Reduced Capacity Top Clamp – Main Vise

24" Solid Discharge Table

3rd Holding Vise on Feed w/ Interlocking Vise Jaws

Hold-Down Roller Assembly

Interlocking Vise Jaws Only

Spray Mist Lubrication

Pedestal Mounted Console

5' or 10' Idle Roller Stock Table

HEM[®] SAW
—The saw that cuts straight.—

www.hemsaw.com

Address: P.O. Box 1148 Pryor OK 74361 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HEM, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HEM, Inc. for a certified dimensional drawing of your specific model.
Copyright 112800 HEM, Inc. All rights reserved.