

Doall C-916M Manual Pivot Type Bandsaw

| | MA | CHINE DIMENSIONS | | | |
|--|--------------|-----------------------|----------|-------------|--|
| Length | | | | 75" | |
| Width | | | | 20" | |
| Height | | | | 43.5" | |
| Weight approx. | | | | 950 Lbs. | |
| | | SPECIFICATIONS | | | |
| | 0° | 45° | 60° | -45° | |
| Round Cutting Capacity | 10 ¾" | | | | |
| Flat Cutting Capacity (H x W) | 9" H x 16" W | | - | - | |
| Square Cutting Capacity | 9" X 16" | | | | |
| | ١ | MACHINE PRICING | | | |
| Blade Tension Gauge | | | | Included | |
| Blade Breakage Switch | | | | Included | |
| Hydraulic Lift Cylinder | | | | Included | |
| Mechanical Vice | | | | Included | |
| Inverter | | | | N/A | |
| Manual Blade Tension | | | | Included | |
| | 0 | PTIONAL FEATURES | | | |
| Blade Brush | | | | Included | |
| Coolant System | | | Included | | |
| Dual Directional Vice for Angle Cuts | | | | N/A | |
| Manual Bundling System | | | | N/A | |
| 6.5ft 2m Feeding Roller Table | | | | N/A | |
| Extra Blades | | | | 4 | |
| Single Roller Stand with Adjustable Height | | | | N/A | |
| | POWER A | ND BLADE SPECIFICATIO | NS | | |
| Main Drive Motor | | | | 2 HP | |
| Hydraulic Motor | | | | | |
| Cutting Speed | | | 1 | 105-275 fpm | |
| Band Dimensions | | | | 1" X 158" | |

RMT | 844-768-3646 | www.RMTUS.com | info@rmtus.com

























www.RMTUS.com Page 1



TERMS / CONDITIONS / DELIVERY / WARRANTY

F.O.B. POINT

To Be Determined

DELIVERY

Stock

PAYMENT TERMS & CONDITIONS

- Sales tax is excluded unless otherwise stated.
- Net on Stock Items.
- Custom orders and special payment terms will vary.
- Prices Exclude overland freight and handling.
- Quoted prices are valid for thirty days from date on quote.
- terms and conditions applies to all quotes and orders.

WARRANTY

30 Day Return Privleage

All Freight - Rigging Cost are Customer responsibility

POINT OF OPERATION GUARDING

Point of operation guarding is the responsibility of the machine owner/user per OSHA Federal Regulation Volume 37-# 202-dated 10/18/72.

INSTALLATION

The customer is responsible for installation of the machine.

ELECTRICAL

208 V 3 Phase/ 60 HZ/ 7.5 Amps

Thank you for the opportunity to provide this quote!

























www.RMTUS.com Page 2