

WATERJET CUTTING SYSTEM

The Techjet-X3® is built to the highest tolerances and incorporates Linear Scale Feedback to ensure the highest accuracy of motion in the industry.





youtube.com/techniwaterjet



twitter.com/techniwaterjet



sales@techniwaterjet.com



www.techniwaterjet.com



Scan the QR code to add TECHNI Waterjet's contact details to your smartphone.



Innovation Through Passion


Techjet - X3 The premium series

FEATURES



REMOTE CONTROL PENDENT (M.P.G)

The Remote Control Pendent makes setting up your waterjet machine fast, simple and accurate.




SERVO Z AXIS

A programmable Z axis with auto height position recall, laser terrain mapping and edge location optics.



TECH-SENSE™

To monitor the cutting head and pause the program prior to any blockage, making "Lights Out" operation a reality.



BREAK AWAY HEAD

Eliminates the risk of damaging the cutting head and scraping material in the event of a crash.

MORE FEATURES

H.P Gauge

The High Pressure Gauge provides water pressure readings to the user.

Water Raise/Lower for Submeraed Cuttina

By raising the water level and submerging the material, "the operating noise level" is reduced below safety limits.

Linear Scale Feedback

This unique feature makes the Techjet X3 range the most accurate waterjet cutting machine on the market.

Diamond Orifice

A diamond will typically give about 1000 hours of trouble free operation compared to a sapphire of approximately 50 hours.





OUANTLM India - Marita

ELECTRIC SERVO PUMP

Core Technology - Proven & Reliable

Quantum NXT™ - 55,000 or 66,000 PSI
The TECHNI Waterjet™ Quantum NXT™
incorporates core "direct servo" technology
that was first applied by NASA for
the Space Shuttle Program.

Quantum NXT[™] Dual - 55,000 or 66,000 PSI TECHNI Waterjet[™] is the first waterjet manufacturer to develop an Electric Servo pump for the waterjet cutting industry.

TJ3000-X3 SPECIFICATIONS

| Machine Size (L, W, H) (Does not include pumps or bulk abrasive hopper) | 4200 x 2350 x 2050 mm (14' x 7' 8" x 6 '8") |
|--|--|
| Machine Weight (empty) | 2010 kg (4440 lbs) |
| Machine Weight (with water) | 6800 kg (14990 lbs) |
| Cutting Table Size | 1550 x 3125 mm (5′ 1″ x 10′ 3″) |
| Cutting Area† | 1525 x 3050 mm (5' x 10') |
| Accuracy of Motion* | ± 0.025 mm (0.001") |
| Repeatability of Motion* | ± 0.015 mm (0.0005") |
| Max Air Speed | 17.5m/min (700 ipm) |
| Max Cutting Speed | 17.5m/min (700 ipm) |
| Max Material Thickness** | 200 mm (8") |

Due to constant endeavour to improve the machine, the specification may be changed without prior notice. *Lineat/Axis. ** 115 mm (4.5") with PAC60 cutting head option fitted.
† Refer to PAC60 specifications.

TJ4000-X3 SPECIFICATIONS

| Machine Size (L, W, H) (Does not include pumps or bulk abrasive hopper) | 4900 x 2650 x 2050 mm (16' x 8' 6" x 6' 8") |
|--|--|
| Machine Weight (empty) | 2330 kg (5140 lbs) |
| Machine Weight (with water) | 8700 kg (19180 lbs) |
| Cutting Table Size | 1860 x 3690 mm (6′ 1″ x 12′ 1″) |
| Cutting Area [†] | 1830 x 3660 mm (6' x 12') |
| Accuracy of Motion* | ± 0.025 mm (0.001") |
| Repeatability of Motion* | ± 0.015 mm (0.0005") |
| Max Air Speed | 17.5m/min (700 ipm) |
| Max Cutting Speed | 17.5m/min (700 ipm) |
| Max Material Thickness** | 200 mm (8") |

Due to constant endeavour to improve the machine, the specification may be changed without prior notice. *Linear/Axis. ** 115 mm (4.5'') with PAC60 cutting head option fitted. † Refer to PAC60 specifications.