



CLEANVAC

CLEANING MACHINES ELECTRIC VEHICLES
industry

MADE IN
TURKEY



www.cleanvac.com

INDUSTRIAL TYPE VACUUM CLEANERS

WD 401 / 501 / 602 / 753

Durable and made of esthetical steel body.
Great power and continuous vacuuming with double fanned by-pass vacuum motors.
Deeply high capacity of cleaning.



INDUSTRIAL TYPE VACUUM CLEANERS & CARPET WASHERS

EWD 501 / 602 / 753

Our EWD series of machines feature industrial type of sweeping such as cleaning carpet and upholstery.



TECHNICAL SHEET

MODEL	EWD 501	EWD 602	EWD 753	WD 501	WD 602	WD 753
Voltage (V – Hz)	220 - 50	220 - 50	220 - 50	220 - 50	220 - 50	220 - 50
Motor Power (Watt)	1.200	2.400	3.600	1.200	2.400	3.600
Clean Water Tank (Lt)	6	8	10	-	-	-
Tank Capacity (Lt)	50	60	75	50	60	75
Air Flow (Lt / min)	3.250	6.500	8.000	3.250	6.500	8.000
Weight (kg)	28	32	40	25	28	33

ASYNCHRONOUS MOTORED HIGH POWER VACUUM SWEEPERS

AS 300 / 400 / 550 / 750 / 1100 / 1500



With asynchronous motored high power machine (mono-phase/Three-phase) 24 hours non-stop working. Thanks to large and effective filtration system that is appropriate to every dust. Vacuuming fallout of industry and opportunity of stock into its large tank.

COMPACT MODELS



TECHNICAL SHEET

Model	Voltage (V ~Hz)	Motor Power (Watt)	Air Flow (Lt/Min)	Suction (mmH2O)	Filter Surface (m^2)	Tank Capacity (Lt)
AS 300	220 - 50 380 - 50	3.000	8.400	2.200	0,35	50
AS 400	380 - 50	4.000	9.200	2.600	1,60	75
AS 550	380 - 50	5.500	11.000	3.100	2,50	75
AS 750	380 - 50	7.500	14.000	4.200	3,50	75
AS 1100	380 - 50	11.000	16.000	4.800	4,50	100
AS 1500	380 - 80	15.000	18.000	5.200	5,40	100

ROTARY BRUSH CARPET SWEEPING MACHINE

RL 400 / 600

Ventilating feature with rotating brush enables the machine to reach and clean the dirt settled in carpets. Absorbing with powerful vacuum helps clean large areas in short time.

Easy to use provides high quality of cleaning in an economic way provides easy reaching to the sides and corners with its long hose. Preferred especially for the cleaning of the carpets of the mosques. Works quite and smoothly with its polyethylene body its a durable industrial type of a machine

TECHNICAL SHEET

MODEL	RL 600	RL 400
Voltage(v-Hz)	220-50	220-50
Total Power	1200Watt	1200Watt
Brush Motor	250watt	250watt
Brush Diameter	60cm	40cm



ROTARY BRUSH

STEAM CARPET&UPHOLSTERY CLEANING MACHINE

ISV 2800 S / 2800 / 4000 / 90 C COMPACT



Our model of ISV 2800-S produces up to 150-170 degrees of steam from its steam generator. Steam helps dissolve dirt in a short period of time and no wetness stays on surfaces. Moisture created by steam also disappears quickly. Along with providing high quality of cleaning, it also disinfects the surfaces with 150 degrees of heat.

TECHNICAL SHEET

MODEL	ISV 2800 - S	ISV 2800	ISV 4000	90 - C COMPACT
Voltage (V)	230 - 50	230 - 50	230 - 50	230 - 50
Motor Power (Watt)	1.400	1.400	1.400	1.400
Dirty Water Tank Capacity (Lt)	20	20	40	10
Clean Water Tank Capacity (Lt)	20	20	50	7
Airflow (Lt/dk)	3.250	3.250	3.250	3.250
Heater (Watt)	3.300	1.200	1.200	3.300
Dimension (cm)	55x93x65	55x93x65	75x85x59	40x46x50
Weight (kg)	44	41	46	20

HOT&COLD HIGH PRESSURE WASHERS

HP 300 / 400 - HD 200 / 250 - IHD 200 / 250

HP Cold water pressure washer is designed to be used for the cleaning of autos, buildings, Tools and different surfaces by using high pressure cold water. Number of pistons : 3 units of ceramic piston. Vertical boiler burner system in hot/cold water models. By-pass unit protects pump motor over pressure. Thermal protector against motor over heat. Thermostatic control for temperature adjustment in hot/cold water models. Detergent and chemical use. Quiet and smooth operation.



TECHNICAL SHEET

MODEL	HP 300	HP 400	HD 200	HD 250	IHD 200	IHD 250
Voltage (V - Hz)	380/50	380/50	380/50	380/50	380 / 50	380 / 50
Motor Power (Kw)	11	18,5	5,5	11	5,5	11
Water Flow (L / dk)	18	20	15	15	15	15
Pressure (Bar)	30 - 300	30 - 400	30 - 200	30 - 250	30 - 200	30 - 250
Motor Speed (d/dk)	1.400	1.400	1.000	1.000	1.000	1.000
Hose length (m)	10	10	10	10	10	10
Dimension (cm)	60x95x61	90x125x90	75x95x65	60x125x60	75x95x65	90x125x90
Weight (Kg)	103	112	80	100	130	170

COLD WATER PRESSURE WASHERS HP SERIES

HP 130 / 140 / 150 / 170 / 200 / 250 / 300 / 400 / 500

HP Cold water pressure washer is designed to be used for the cleaning of autos, buildings, Tools and different surfaces by using high pressure cold water. Number of pistons : 3 units of ceramic piston. Vertical boiler burner system in hot/cold water models. By-pass unit protects pump motor over pressure. Thermal protector against motor over heat. Thermostatic control for temperture adjustment in hot/cold water models. Detergant and chemical use. Quiet and smooth operation.



TECHNICAL SHEET

MODEL	HP130	HP 140	HP 150	HP 170	HP 200	HP 250	HP 300	HP 400	HP 500
Voltage (V – Hz)	220-50/60	220 – 50/60	220 – 380 50/60	380 50/60	380 50/60	380 50/60	380 50/60	380 50/60	380 50/60
Total Power (Kw)	1,5	2,2	3	4	5,5	7,5	11	18,5	18,5
Water Flow (Lt / min)	5	9	11	13	14	15	17	20	21
Pressure (Bar)	130	140	150	170	200	250	300	400	500
Brush rpm (min)	1400	1400	1400	1400	1400	1400	1400	1400	1400
Material	P. Rotation	P. Rotation	P. Rotation	P. Rotation	P. Rotation	P. Rotation	S. İnox	S. İnox	S. İnox
Weight (kg)	30	40	50	56	62	68	80	100	94

HOT&COLD HIGH PRESSURE WASHERS

IHP 150 / 200 / 250 / 300 & AUTO DS 1000 / 1500

Hot & cold water high pressure washers those have pressures starting 150 bar up to 1000 bars are available in our range of hot water pressure washers for mainly industrial and commercial use. IHP 150, IHP 170, IHP 200, IHP 250 and IHP 300 are the models for both hot and cold water wash need having following specifications.



TECHNICAL SHEET

MODEL	IHP 100	IHP 170	IHP 200	IHP 250	IHP 300 (Krom)
Voltage (V – Hz)	230-380/50	380/50	380/50	380/50	380 / 50
Motor Power (Kw)	3	4	4	7,5	11
Water Flow (L / dk)	8	10	14	16	18
Pressure (Bar)	30 - 150	30 - 170	30 - 200	30 - 250	30 - 300
Motor Speed (d/dk)	1.400	1.400	1.400	1.400	1.400
Hose Length (m)	10	10	10	10	10
Dimension (cm)	78x78x96	78x78x96	78x78x96	78x78x96	90x125x90
Weight (Kg)	103	112	118	138	173

DRY STEAM CAR WASHING MACHINE

AUTO DS 1000 / 1500

Steam car washing machine AUTO DS1500 generates high pressure steam of 170 degrees hot, not only cleans also disinfects the surface.



TECHNICAL SHEET

MODEL	AUTO DS 1000	AUTO DS 1500
Voltage (V / Hz)	380 / 50-60	380 / 50-60
Pressure Pump (A)	5,5	5,5
Clean Water Tank Capacity (lt)	50	50
Steam Resistance (Watt)	10.000	15.000
Steam Pressure (bar)	8	8
Debi (lt / dk)	1,5	1,5
Dimension (cm)	75 x 85 x 59	75 x 85 x 59
Weight (kg)	61	62

FLOOR SCRUBBING & POLISHING MACHINE

SC 42 / 43 / 43D / 50

To be used for the purpose of cleaning and polishing of floors (marble,pvc,-mosaics etc.) also brushing, scrubbing and cleaning of carpets. Provides an easy and quiet operation models with belt drive and gear box These are professional scrubbing and polishing machines for business centers,markets,schools,factories,hospitals and cleaning companies.



TECHNICAL SHEET

MODEL	SC 42	SC 43	SC 43 - D	SC 50
Voltage (V - Hz)	220 - 50	220 - 50	220 - 50	220 - 50
Total Power (Kw)	0,75	1,1	2,2	2,2
Working Width (cm)	42	43	85	50
Brush rpm (min)	170	170	170	170
Weight (kg)	30	40	80	50
Brush Diameter	42	43	85	50
Tank Capacity (Lt)	12	12	12	-
Dimension (cm)	45x60x120	45x60x120	80x60x120	55x65x125



BATTERY POWERED & CABLED HARD FLOOR SCRUBBER DRYER

E - B / 3501 / 4501 / 7501 / ESC 42

TECHNICAL SHEET

MODEL	E 3501	B 3501	E 4501	B 4501	E 7501	B 7501	ESC 42
Brush Motor (Volt / Watt)	220 / 800	24 / 400	220 / 800	24 / 400	220 / 800	24 / 400	220 / 800
Vacuum Motor (Volt / Watt)	220 / 1200	24 / 600	220 / 1200	24 / 600	220 / 1.200	24 / 600	220 / 1.200
Clean / Dirty Water Tank (Lt)	20 / 30	20 / 30	35 / 45	35 / 45	65 / 75	65 / 75	8 / 10
Brush Quantity / Diameter (cm)	1 - 38	1 - 38	1 - 43	1 - 43	1 - 43	1 - 43	1 - 38
Brush rpm	170	170	170	170	170	170	170
Working Width (mm)	670	670	770	770	770	770	400
Max. Performance (m ² / h)	1.500	1.500	2.000	2.000	2.500	2.500	1.000
Battery (V/Ah)	-	24 / 80	-	24 / 100	-	24 / 100	-



Battery powered and cabled hard floor scrubber dryer E & B series are walk behind scrubber for professional floor cleaning purposes in large areas.



RIDE ON HARD FLOOR SCRUBBER & DRYER

B 9001 / 11001 / 12001



Ride-on hard floor scrubber dryers B 9001 and B 12001 are ideal for use in large areas factories, business centers, warehouses, hospitals, hotels, schools and many places. They are battery powered scrubber dryers providing ease of use and saving on operation costs

TECHNICAL SHEET

MODEL	B 9001	B 11001	B 12001
Brush Motor (Volt/watt)	24/400	24/400	24/400
Vacuum Motor (Volt/watt)	24/800	24/800	24/800
Clean/Dirty Water Tank (Lt)	70/80	900/100	100/100
Brush Quantity/Diameter (cm)	2/38	2/43	2/43
Brush Rpm	170	170	170
Vacuum Suction width (mm)	800	1050	1050
Working Speed (km/h)	0-5	0-5	0-5
Max Performance (m ² /h)	3500	4500	5000
Working Motor (Volt/watt)	24/400	24/400	24/400
Battery (V/ah)	24/400	24/400	24/400

RIDE ON HARD FLOOR SCRUBBER & DRYER

BS 1450



Battery powered sweepers are ideal for use in large areas factories, business centers, warehouses, hospitals, hotels, schools and outside sweeping. They clean 10.000m² area / hour with one charge.

TECHNICAL SHEET

MODEL	BS 1450
Brush Motor (Volt/watt)	24/400
Tank Capacity (Lt)	150
Brush Quantity	2 Disc 1 Rolling
Brush Rpm	170
Vacuum Suction Width (mm)	800
Working Speed (km/h)	0 – 8
Max Performance (m ² /h)	10000
Working Motor (Volt/watt)	24/1000
Battery (V/ah)	24/250

BATTERY POWERED OUTDOOR SWEEPER

ST 240

Outdoor vacuum cleaner is a mobile, very easy to handle and self-propelled machine, able to collect all kinds of waste.

It vacuumed with both industrial and urban waste: paper, cardboard, cigarette packets and butts, cans and glass, plastic or metal bottles, dog faeces, dead leaves, waste trapped in tree grills, wood.

Outdoor vacume cleaner has established itself as an essential tool for cleaning pavements, streets, alleyways, parks, tree grills, markets, factories, workshops, car parks, halls, rooms, platforms, train stations, airports etc.

TECHNICAL SHEET

MODEL	ST 240
Tank Capacity	220 / 250 lt
Motor Type	2 Motor Driver and Vacuum
Battery Type	6 V gel 4 cell (24 V)
Operation Time	8 – 12 hours
Speed	6 km/h
Suction Hose diam.	115 mm
Suction hose type	Impact Resistant
Body Material	Polyester
Dimention (cm)	170x80x160



BATTERY POWERED TRASH TAXI

CT 2000

The improved garbage collector (trash taxi) is ideal for use in factories, hotels, municipalities etc. Available from 1m³ to 3m³ capacity.



TECHNICAL SHEET

MODEL	CT 2000 ELECTRIC TRASH TAXI
Full Charge Time	8 – 10 Hour
Distance	50 – 60 Km
Motor Power	6 Kw
Battery	50 AH (24 X 2V Cell)
Tire Dimension	700 – 16
Net Weight	2.400 Kg
Dimension (cm)	339 x 198 x 119
Speed	0 – 40 Km/Hour
Garbage Tank Capacity	1,75 M ³
Carriage Capacity	450 Kg
Trash Disposal Height	150 Cm
Working System	ELECTRICITY

STREET SWEEPING VEHICLE

ST 750 / 1000 / 1500

Low investment cost
Special production upon request and business type
High vacuum system
Fastly garbage disposal
High maneuverability
Easy to operate and maintenance
Electric, Diesel and Fuel models

TECHNICAL SHEET

Model	ST750	ST1000	ST1500
Total Power	34 kw	44 kw	48 kw
Sweeping Speed	0-10 km	0-10 km	0-10 km
Working Speed	20 km	25 km	25 km
Sweeping Width	1400 mm	1400 mm	1600 mm
Tank Volume	0,75 m ³	1 m ³	1.5 m ³
Fuel Tank Capacity	50 Lt	50 Lt	60 Lt



STREET SWEEPING VEHICLE

ST 2500 / 4000 / 6000

- Low investment cost
- Special production upon request and business type
- High vacuum system
- Fastly garbage disposal
- High maneuverability
- Easy to operate and maintenance
- Electric, Diesel and Fuel models



TECHNICAL SHEET

Model	ST2500	ST4000	ST6000
Total Power	60 kw	80 kw	100 kw
Sweeping Speed	0-10 km	0-10 km	0-10 km
Working Speed	25 km	25 km	25 km
Sweeping Width	2000 mm	2200 mm	2200 mm
Tank Volume	2.5 m ³	4 m ³	6 m ³
Fuel Tank Capacity	70 Lt	100 Lt	100 Lt

DIESEL & BATTERY POWERED FORKLIFTS

DX 30 - 30 / 30 - 45 B 20 - 30

- Models with 1 carrying capacity up to 16 tons
- Dublex - Triplex models
- Diesel & Battery Powered Options
- Common Service



TECHNICAL SHEET

MODEL	DX 30-30	DX30-45	D30-45	B20-30
Motor	Xinchang C490BPG Dizel Motor	Xinchang C490BPG Dizel Motor	Isuzu C240 Dizel Motor	Akülü Curtis Sürücü
Lifting Capacity	3.000 kg	3.000 kg	3.000 kg	2.000 kg
Load Center	500 mm	500 mm	500 mm	500 mm
Rated Power	36.8 kW	36.8 kW	35.4 kW	-
Max. Lift Height	3.000 mm	4.500 mm	4.500 mm	3.000 mm
Mast Lift Speed	450 mm/s	450 mm/s	450 mm/s	280 mm/s
Driving Speed	19 km/saat	19 km/saat	19 km/saat	14 km/saat
Rotation Angle	2.465 mm	2.465 mm	2.465 mm	2.200 mm
Base Height	140 mm	140 mm	140 mm	110 mm
Vehicle Length(Without Forks)	2.744 mm	2.744 mm	2.744 mm	2.416 mm
Forklift Width	1.220 mm	1.220 mm	1.220 mm	1.150 mm
Peak Protection	2.090 mm	2.090 mm	2.090 mm	2.172 mm
Distance Between Axles	1.740 mm	1.740 mm	1.740 mm	1.520 mm
Front Axle Length	474 mm	474 mm	474 mm	466 mm
Fork Measures (mm)	40x120x1070	40x120x1070	40x120x1070	40x120x1070
Service Weight	4.470 kg	4.470 kg	4.470 kg	3.850 kg

BATTERY CARGO CARRYING BASKET

CR 600



For factories , airports, otels, holiday vil-
lages, publics, hospitals etc places is de-
veloped also up to 1000 kg carry capacity
battery cargo carrying basket

TECHNICAL SHEET

MODEL	CR 600
Case Length	120 cm
Width	82 cm
Case height	80 cm
Height from Floor	40 cm
Motor Power	800 Watt
Battery	24 Volt 40 Ah
Rear Wheels	3.50 - 6 (inner tube)
Front Wheels	3.00 - 4 (Inner tube)

TOW TRACTOR

Tow Tractor for handling material into and out of the plant

- Tow Tractor is a powerful, versatile and economic tow tractor for pulling trailers up to 6 Tons.
- It provides optimum traction at all times, even in industrial floors or outdoor areas such airport.
- It has effortless driving with either hand, safely and ergonomically.
- Also automatically reduce speed when cornering, to keep always driving in safe conditions.



*We can be able to
manufacture different
power tow tractors on
customer demands*



BATTERY POWERED ENTERTAINMENT VEHICLES

LONDON BUS ENTERTAINMENT VEHICLE

GENERAL FEATURES

Type of Vehicle	17 Children Capacity
Type	Type Electric Entertainment Vehicle
Battery Weight	(25kg x 4) 100 kg
Seating Capacity	18
Color	Red

FEED - POWER PROPERTIES

Motor	Zibo Super Motor Co. Ltd.
Motor Output Power	4 Kw 48 V
Battery	4 x (XINNENG 12 V 150A)
Charger	MRS

ŞASE

Frame	Iron
Cover	Fiberglas
Steer	Differential Routing
Break system	Mechanical
Seats	Leather
Vehicle Lighting	Led

PERFORMANCE

Maks Direction Speed	26 km/h
Maximum return Speed	15 km/h
Return Grade	6,4 m
Full charge time	6 h
Full Charge Avg. Distance	0 - 40 km
Angle of climb	12 °
Motor Break	Optional

DIMENTIONS

Length	390 cm
Width	124 cm
Height	242 cm
Base Height	15,5 cm
Wheels	4 - Golf - 18 x 8,5 - 8
Min Height	12 cm



ELECTRIC LOAD AND PASSENGER TRANSPORT VEHICLES

B 30 - 2 / 40 - 4 / 40 - 6



TECHNICAL SHEET

MODEL	B 30 – 2	B 40 – 4	B 40 – 6
Motor (kW)	3	4	5
Speed (KM)	25	25	25
Maximum Range (KM)	35 – 40	35 – 40	35 – 40
Battery Voltage (V)	48	48	48
Transmission	Direct drive, double reduction, helical gear		
Steering	Self-adjusting, Rack and Pinion Gear		
Suspension	independent leaf spring with dual hydraulic shock absorber		
Front - Rear Brake	Mechanical braking on 4 wheels foot - controlled parking brake		
Chassis	80 ° NPI Corrosion-resistant coating		
Signal, Horn, Headlight, Reverse - Forward, Complete Transparent Closure			

In factories, open spaces, campsites on sites, hospitals, we provide alternative solutions to the transportation of cargo and passengers in places.

- Quite work
- Economic
- Eco Friendly
- Easy to use
- Purposeful custom production
- Suitable alternatives that do not require maintenance

ELECTRIC LOAD AND PASSENGER TRANSPORT VEHICLES

B 60 - 8 / 80 - 10 / 100 - 12



TECHNICAL SHEET

MODEL	B 60 – 8	B 80 – 10	B 100 – 12
Motor (kW)	6	8	10
Speed (KM)	25	25	25
Maximum Range (KM)	35 – 40	40 – 50	40 – 50
Battery Voltage (V)	48	48	48
Transmission	Direct drive, double reduction, helical gear		
Steering	Self-adjusting, Rack and Pinion Gear		
Suspension	independent leaf spring with dual hydraulic shock absorber		
Front - Rear Brake	Mechanical braking on 4 wheels foot - controlled parking brake		
Chassis	80 ° NPI Corrosion-resistant coating		
Signal, Horn, Headlight, Reverse - Forward, Complete Transparent Closure			

Whether 2 or
16 People

4 TL İLE
50 KM MENZİL

BATTERY POWERED BIKES

T 150 / TK 150 / S 150



AIR CRAFT VACUUM CLEANERS

90 C



Energy : 110V
Motor : 1250 W
Tank Capacity / Disposal Paper : 7lt / 12lt
Air Flow : 35lt/s
Weight : 7kg
Cable Length : 10m
Sound Level : 78db
Filter System : Cartridge Filter
Dimension : 33*40*40cm



**FROM DESIGN TO
PRODUCTION**

TEKTEM MAKİNA
SAN. VE DİŐ TİC. LTD. ŐTİ

ESENŐEHİR MAH. NECİP FAZIL BULVARI NO:23
Y.DUDULLU ÜMRANİYE / İSTANBUL
TURKEY

PHONE : +90 216 499 90 90 pbx

info@cleanvac.com



+90 555 980 80 00

WhatsApp

www.cleanvac.com

