

ML26/160

- Combination Lathe
- Swing: 27"
- Spindle Bore: 6"
- Control : 8200-B



Shown with options



MILLTRONICS USA
LET'S INVENT

1400 Mill Lane | Waconia, MN 55387 | Sales@milltronics.com | 888.999.1440 | www.milltronics.com

SPECIFICATIONS:

CAPACITY:	
X/Z Travels	13" / 163" (330 / 4140 mm)
Swing Over Bed	27" (685 mm)
Swing Over Gap	34.2" (870 mm)
Gap Distance	12.75" (320 mm)
Swing Over Cross Slide	16.1" (410 mm)
SPINDLE:	
Spindle Nose	A2-11
Spindle Bore	6" (153 mm)
Spindle Range	30-1600 RPM
AC Spindle Motor	24/15 HP (18/11 kW) 2 Speed Delta/WYE
Spindle Torque	1250 ft-lbs (1690 N.m)
TAILSTOCK:	
Tailstock Quill Travel	6" (150 mm)
Tailstock Quill Diameter	3.94" (100 mm)
Tailstock Quill Taper	MT5
OPTIONAL TURRET:	
Number of Tools	8
Tooling Size	1" (25 mm)
Boring Bar Capacity	1.5" (38 mm)
Tool Selection	Bi-directional
MOTION:	
X/Y/Z Axis Rapid Traverse Rate	500 IPM (12.7 m/min)
Max. Cutting Feed Rate	100 IPM (2540 mm/min)
X Axis Ballscrew Diameter	1.25" (32 mm)
Y Axis Ballscrew Diameter	1.97" (50 mm)
Positioning Accuracy	+/- 0.00025" (+/- 0.0063 mm)
Repeatability	0.0002" (0.005 mm)
Axis Thrust Force X, Z	4000 lbs. (1815 kg)
GENERAL:	
Machine Height	83" (2108 mm)
Floor Space Required (W x D)	246" x 84" (6250 x 2133 mm)
Machine Weight	17,200 lbs. (7800 kg)
Power Required	30 KVA / 80 amps
Voltage Required	208-240 Volts / 3 Phase

MACHINE STANDARDS:

- Milltronics 8200-B series CNC control
- Solid box way bed construction
- 1600 RPM spindle
- Tailstock
- Auto lubrication
- Single sliding door enclosure design
- 6" Spindle bore w/ A2-11 Nose
- Rear mount chuck flange
- 12" LCD color display
- Chip conveyor w/wash down
- Spindle load meter
- Flood coolant
- Solid model graphic display
- USB Port
- Gap bed design
- 8 Station 1" automatic turret
- LCD hour meter
- Thread chasing feature
- One year warranty
- Constant Surface Speed (CSS)



8200-B CNC

The new standard of control

With its conversational programming, onscreen help, intuitive menus, color graphics and prompted tool settings, the 8200-B CNC helps new operators train faster and become more productive sooner. Shops can choose either conversational, G-code programming, or download tool paths created with a CAM system - whatever is the most efficient way to produce the required part.

CONTROL STANDARDS:

- PC-based 8200-B CNC includes 1 GB parts storage memory
- Enhanced CPU with Block processing speed of 2000 bps with enhanced jerk control and look ahead
- Conversational plus G & M code programming including coordinate rotating, scaling, mirror image, thread mill engraving, helical interpolation, auto routines, and user definable macros with trig assist and irregular pocket clearing
- 12" LCD active matrix color display
- Auto DXF file import
- 3D part and wire frame tool path graphics plus solid modeling graphics
- Management software that allows editing of very large programfiles at the machine
- Spindle loader meter
- User definable macros with trig assist
- USB connectivity
- MTConnect compliant
- Networking

Distributed By: