

RH30

3 Axis CNC Bed Mill

- Table : 73" x 24"
- Travels : 60" x 30" x 28"
- Control : 8200-B



Shown with options



MILLTRONICS USA
LET'S INVENT

1400 Mill Lane | Waconia, MN 55387 | Sales@milltronics.com | 888.999.1440 | www.milltronics.com

SPECIFICATIONS:

CAPACITY:

X/Y/Z Travels	60 x 30 x 28" (1525 x 760 x 710 mm)
Table Size	73 x 24" (1850 x 610 mm)
Allowable Table Load	3000 lbs. (1360 kg)
T-Slot Size	.71" (18 mm)

SPINDLE:

Spindle Gage Line to Table Distance	2.5-30.5" (65-775 mm)
Column to Spindle Center	30.5" (775 mm)
Spindle Taper	ISO No. 40
Spindle Speed (Std)	8,000 RPM
Spindle Speed (Opt)	15,000 RPM
AC Spindle Motor	24/15 HP (18/11 kW) 2 Speed Delta/WYE
Spindle Torque (Std W/ 8,000 RPM)	250 ft-lbs (339 N.m)

MOTION:

X/Y/Z Axis Rapid Traverse Rate	500/400 IPM (12/10 m/min)
Max. Cutting Feed Rate	300 IPM (7.6 m/min)
Positioning Accuracy	+/- 0.00039" (+/- 0.010 mm)
Repeatability	0.0002" (0.005 mm)
Axis Thrust Force X/Y/Z	3000/4000 lbs. (1360/1800 kg)

OPTIONAL AUTOMATIC TOOL CHANGER

ATC Type	24 Carousel
Tool Shank	CT40
Pull Stud	MAS 60° Retention Knob Style -Flange 40 Taper
Max. Tool Diameter	3.5" (80 mm)
Max. Tool Length	7" (175 mm)
Max. Tool Weight	15 lbs. (7 kg)

GENERAL:

Machine Height	106" (2695 mm)
Floor Space Required (W x D)	169 x 99" (4293 x 2515 mm)
Machine Weight	11,000 lbs. (5000 kg)
Power Required	30 KVA / 80 amps
Voltage Required	208-240 Volts / 3 Phase

MACHINE STANDARDS:

- Milltronics 8200-B Series CNC control
- 12" LCD color display
- Solid model graphic display
- 1 GB program storage memory
- DXF file import
- Networking
- Solid Way Construction
- 8000 RPM spindle
- X/Y axis metal way cover construction
- Auto lubrication
- CT40
- 24/15 HP 2 speed spindle motor
- Spindle load meter
- Spindle air purge
- Flood Coolant
- Rigid tapping
- LCD hour meter
- One year warranty



8200-B CNC

The new standard of control

With its conversational programming, onscreen help, intuitive menus, color graphics and prompted tool settings, the 8200-B CNC helps new operators train faster and become more productive sooner. Shops can choose either conversational, G-code programming, or download tool paths created with a CAM system - whatever is the most efficient way to produce the required part.

CONTROL STANDARDS:

- PC-based 8200-B CNC includes 1 GB parts storage memory
- Enhanced CPU with Block processing speed of 2000 bps with enhanced jerk control and look ahead
- Conversational plus G & M code programming including coordinate rotating, scaling, mirror image, thread mill engraving, helical interpolation, auto routines, and user definable macros with trig assist and irregular pocket clearing
- 12" LCD active matrix color display
- Auto DXF file import
- 3D part and wire frame tool path graphics plus solid modeling graphics
- Management software that allows editing of very large programfiles at the machine
- Spindle loader meter
- User definable macros with trig assist
- USB connectivity
- MTConnect compliant
- Networking

Distributed By: