

GMC DELUXE HYDRAULIC SHEARS

Model # HS-0810MD, 8' x 10Ga., 5-1/2HP , 220V/440V, 3ph

Standard Features:

- Taiwan machines
- ISO 9001 certified
- HD all steel construction for maximum rigidity
- German logic quiet Rexroth hydraulic system
- Adjustable stroke from 16-20 strokes per minute
- 60" long squaring arm with inch / mm scale
- Spring hold-downs
- high grade carbon/chrome alloy steel blades and hardened to 62 hrc, 2-edge indexable upper blade and 2-edge indexable bottom blade
- Full length with full view finger guard
- Front supports and (2) side gauges
- Safety type foot pedal control
- Jog, single continuous auto operation modes
- One year warranty for parts

Standard Equipment:

- 26" manual back gauge with inch/metric dual scale & one side operated hand wheel
- 60" long squaring arm with inch / mm scale
- 2 each 24" front support arms
- 2 each 14" Side gauges with inlaid inch/metric dual scale
- Spring independent hold-downs
- full length finger guard
- Removable safety foot pedal control
- One set of blades

Optional Equipment:

- Safety fence for enclosure of the back side of the machine..... \$
- Special blade set for stainless steel for HS-0412MD/0410MD/0610MD \$
- Special blade set for stainless steel for HS-0810MD/1010MD..... \$

Specifications:	HS-0610MD	HS-0810MD
Cutting capacity: mild steel	6'x 10Ga	8'x10Ga
stainless steel	6'x 14Ga	8'x14Ga
Blade length	6'6"	8'2"
Strokes per minute adjustable	16-20	14-18
Throat depth	16"	16"
Worktable height	30-1/2"	30-1/2"
Front support arm	24"	24"
Back gauge, manual	26"	26"
blade rake angle	1.5 degree	1.5 degree
oil tank cap.	21Gal.	26Gal.
Main motor	5-1/2HP	5-1/2HP 220V / 440V , 3 phase
Machine weight	4,150 LBS	5,650LBS
Machine dimensions	98x35x52"	118x35x52"

