GMC

HEAVY DUTY HYDRAULIC SHEAR

Model # HS-0410E, 4' x 10Ga, 7-1/2 HP, with 24" SIKO power back gauge …

Standard Features:

- **ISO 9001 certified**
- **Taiwan machines**
- **24" German SIKO Front Operated power back gauge w/ micro adjustment 0.004" , inch/mm digital display**
- **Quick Change Blade Gap Adjustment (BGA), with gap dial**
- **CE standard "OMERO" electric control system**
- **Meet OSHA safety standard code**
- **Shadow line for accurate straight cutting**
- **Adjustable cutting length and stroke**
- **Ball transfer plates on worktable for easy loading workpiece**
- **Well balanced and sturdy all steel machine frame**
- **German made Hydraulic logic system centrally located and quiet**
- **Hydraulic hold-downs with anti-mar neoprene**
- **Shear blades are high grade carbon/chrome alloy steel and hardened to 60 HRC, 2-edge indexable upper blade and 2-edge indexable bottom blade**
- **Full length viewable safety finger guard to protect operator from cutting hazard**
- **Removable safety foot pedal, automatic blade raise up on removal of foot from pedal**
- **Hydraulic, electrical overload protection**
- **Compact operator control panel**
- **All motors are overload protected & low voltage control system**
- **Jog or continuous auto cycle cutting operation modes**
- **One year industrial warranty for parts**

Standard Equipment:

- 24" German SIKO Front Operated Power Back Gauge with micro adjustment , accuracy 0.004" inch/metric digital display.
- 1 each 60" squaring arm with inlaid inch/metric dual scale
- Quick change blade gap adjustment (BGA) with gap dial
- Shadow line for accurate straight cutting
- Material support and drop back chuter
- Upper and bottom blade set with 2-edge on bottom & 2-edge on upper
- 2 each 24" front support arms
- Hydraulic hold-downs with anti-mar neoprene
- Full length viewable finger guard
- Removable safety foot pedal
- Tool box ☐

Optional Equipment:

- Safety fence for enclosure of the back side of the machine…… $

GMC HEAVY DUTY HYDRAULIC SHEAR

Specifications:	**HS-0410E**
Cutting capacity: mild steel stainless steel	 4'x10Ga 4'x14Ga
Blade length	4'4"
Strokes per minute	12-20
Worktable height	34-1/2"
Front support arm	24"
Back gauge	24" German SIKO Power Back gauge
blade rake angle	2.0 degree
Oil tank capacity	17 Gal
Main motor Motor for power back gauge	7-1/2HP, 220V / 440V , 3 phase 3/4 HP, 220V/440V, 3 phase
Machine weight	5,150LBS
Machine dimensions	74x86x63"

