



NC Hydraulic Box & Pan Brake

Sales Prices:

HBB-1010NC, 10x10Ga. 48" NC table back gauge

Standard Features:

- ISO 9001 certified
- Meet OSHA and CE safety standard
- 48" NC table back gauge with fingers
- Max. 16 bends per program
- Upto 100 Program Storage
- Programmable Angle/ Angle Correct
- NC ram height control for open hemming
- Hardened fingers and table
- Germany Rexroth hydraulic system
- Yaskawa Servo motors and Drives
- Schneider electrical components
- All steel construction for maximum rigidity
- Hydraulic logic system centrally located and quiet
- Safety type foot pedal with handle and E-stop switch
- Safety 24V low voltage & overload protection
- One year industrial warranty for parts

Optional Equipment:

One piece 10' straight finger ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, \$

Specifications:	HBB-1010NC	
Capacity Mild Steel Stainless Steel Hemming max thickness	10Ga. 12Ga. 20Ga.	
Bending length capacity	10'	
Bend Angle Degree, programmable	135 degree	
Max. Box Depth	6"	
Large Beam Opening/clamping opening	3"	
Beam front/back adjustment	1"	
Min. Reverse Bend	1"	
Max. Table Back Gauge Distance Max. Table Back Gauge Distance	48-3/8" 1/4"	
Back Gauge Repeatability	0.0039"	
Back Gauge Table height	35-3/4"	
Assorted fingers	3"/4"/5"/6"	
Main motor Servo motor for back gauge	10HP 1HP	
Hydraulic oil tank capacity	32 Gal.	
Machine weight , LBS Machine size, L x W x H	8,850 LBS 175x93x89"	





