

CLAMPING TOWERS - Located in D-29223 Celle	Length	Holes on length side	Distance between holes	Width	Holes on width side	Distance between holes	Hight
Tower A - with stand	1200 mm			1200 mm	416	50	1435 mm
Without stand	700			800 mm			1300 mm
Connections		4	450 mm				
Tower B - with stand	1200 mm	21	200 mm	1200 mm	28	200 mm	1660 mm
Without stand	600 mm			800 mm			1600 mm
Tower C - with stand	1250 mm	35	200 mm	990 mm	20	200 - 140 mm	1660 mm
Without stand	1250 mm			300 mm			1600 mm
Tower D - with stand	1250 mm	35	200	990 mm	20	200-140 mm	1660 mm
Without stand	1250 mm			990 mm			1600 mm
Tower E - with stand	1260 mm	28	200	1250 mm	21	200	1660 mm
Without stand	800 mm			600 mm			1600 mm
Tower F - with stand	1250 mm	42	200	910 mm	20	200-140 mm	1660 mm
Without stand	1250 mm			300 mm			1600 mm
Tower G - with stand	1250 mm	42	200	910 mm	20	200-140 mm	1660 mm
Without stand	1250 mm			300 mm			1600 mm
Tower H - with stand	1100 mm			710 mm	5 per side		1500 mm
(larger plate - top part)	View from front	top 80	50 mm				
(smaller plate)	View from front	394	45 mm				
(larger plate)	Backside	65	diverse		2 connection	850 mm	
Without stand	1100 mm			335 mm			1450 mm
Tower I - with stand	1100 mm	10	850-425 mm	720 mm	82	50 mm	1410 mm
second stand (bottom)			900 mm				
Without stand	1100 mm			200 mm			1360 mm

SOLD

SOLD